



| SPEZIFIKATION | VERBINDUNG | UNIPOLAR |
|--|------------|------------|
| AMPS/PHASE | | 0.40 |
| RESISTANCE/PHASE(Ohms)@25°C | | 30.00±10% |
| INDUCTANCE/PHASE(mH)@1KHz | | 25.00±20% |
| HOLDING TORQUE(Nm)[lb-in] | | 0.32[2.83] |
| LINEAR TRAVEL/STEP(mm) | | 0.01 |
| STEP ANGLE(°) | | 1.80 |
| STEP ACCURACY(NON-ACCUM) | | ±5.00% |
| ROTOR INERTIA(g-cm ²) | | 68.00 |
| WEIGHT(Kg)[lb] | | 0.35[0.77] |
| TEMPERATURE RISE:MAX.80°C (MOTOR STANDSTILL;FOR 2PHASE ENERGIZED) | | |
| AMBIENT TEMPERATURE -10°C~50°C[14°F~122°F] | | |
| INSULATION RESISTANCE 100 Mohm (UNDER NORMAL TEMPERATURE AND HUMIDITY) | | |
| INSULATION CLASS B 130°C[266°F] | | |
| DIELECTRIC STRENGTH 500VAC FOR 1MIN.(BETWEEN THE MOTOR COILS AND THE MOTOR CASE) | | |
| AMBIENT HUMIDITY MAX.85%(NO CONDENSATION) | | |

| STEP | A | B | \bar{A} | \bar{B} | $\text{O}(\bar{\text{O}})$ | CW |
|------|---|---|-----------|-----------|----------------------------|----|
| 1 | + | + | | | + | |
| 2 | | + | + | | + | |
| 3 | | | + | + | + | |
| 4 | + | | | + | + | |
| 1 | + | + | | | + | |



| | | | |
|-------|-----------|--|------------|
| | APVD | | 10.19.2021 |
| | CHKD | | |
| 1:1 | DRN | | |
| SCALE | SIGNATURE | | DATE |

STEPPER MOTOR
17E19S0406AB-300RA
 (17LS19-0406E-300Y)