






SPECIFICATION \ CONNECTION		BIPOLAR	
VOTAGE(VOC)		3.36	
AMPS/PHASE		2.10	
RESISTANCE/PHASE(Ohms)@25°C		1.60±10%	
INDUCTANCE/PHASE(mH)@1KHz		3.00±20%	
HOLDING TORQUE(Nm)[lb-in]		0.65[5.75]	
STEP ANGLE(°)		1.80	
STEP ACCURACY(NON-ACCUM)		±5.00%	
ROTOR INERTIA(g-cm²)		82.00	
WEIGHT(Kg)[lb]		0.50[1.10]	
TEMPERATURE RISE:MAX.80°C（MOTOR STANDSTILL;FOR 2PHASE ENERGIZED）			
AMBIENT TEMPERATURE -10°C~50°C[14°F~122°F]			
INSULATION RESISTANCE 100 Mohm（UNDER NORMAL TEMPERATURE AND HUMIDITY）			
INSULATION CLASS B 130°C[266°F]			
DIELECTRIC STRENGTH 500VAC FOR 1MIN.(BETWEEN THE MOTOR COILS AND THE MOTOR CASE)			
AMBIENT HUMIDITY MAX.85%(NO CONDENSATION)			
1:1			
SCALE			

TYPE OF CONNECTION (EXTERN)		MOTOR	
PIN NO	BIPOLAR	LEADS	WINDING
1	A —	BLK	
2	A\ —	GRN	
3	B —	RED	
4	B\ —	BLU	

FULL STEP 2 PHASE-Ex. ,
WHEN FACING MOUNTING END (X)

STEP	A	B	A\	B\		
1	+	+	-	-		
2	-	+	+	-		
3	-	-	+	+		
4	+	-	-	+		



APVD						STEPPER MOTOR
CHKD						
1:1		DRN				
SCALE		SIGNATURE		DATE		17HS24-2104S